

Prompter PR34

A three way
full power solution

- SA 8535 Ribbon Compact Driver™
- Multi Color Option
- Pre wired for Dynamic Damping control
- Dynamic Power Handling
- High acoustic output



| | |
|---------------------------------|--|
| Frequency response | 56Hz - 30kHz (+/- 3dB) |
| Drivers | 1 x SA1213N neodym LF driver 1 x SA8535 neodym MF/HF driver |
| Cross-over frequency | 1200 Hz |
| Nominal impedance | 8 Ohm |
| Sensitivity @ 1W/1m | 98 dB |
| Max. RMS power | 400 W |
| Max. Peak power | 1000 W |
| SPL program/peak | 124/129 dB |
| Dispersion (2 kHz H x V) | 90° x 70° |
| Color | SA Black, other colors on request |
| Front | Expanded metal grill + acoustic transparent cloth |
| Connectors | 2 x 4-pole Speakon |
| Physical dimensions (h x w x d) | 380 x 671 x 344 mm (15.0 x 26.4 x 13.5 in.) |
| Weight | 19,5kg (43.-0 lb) |

Design may work well on paper, but the actual quality of the product depends on the quality of the manufacturing process. SA holds to one of the tightest manufacturing standards in the industry. The result is that products of the same model have identical specifications. The often boasted professional audio phrase "a matched pair" does not apply to SA. All speakers of the same model are identical. All components are tested separately, and so are the final products. These quality tests are done both manually and by computer, and have a strict maximum tolerance of 1 dB! A sound check and a visual end inspection are part of the quality control process.



That's How Music Should Sound !